

Typenschlüssel/Bestellangaben

| Parameter Ausstattung | Beschreibung Ausführung | Bestellcode | PWG 10 | PWG 12 | PWG 16 | PWG 20 | PWG 25 | PWG 32 | PWG 44 | PWG 63 | PWG 73 | PWG 100 |
|-----------------------|-------------------------|-------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---------|
| Spindelsteigung | 1 mm | | 1 | 1 | 1 | 1 | 1 | | | | | |
| | 1,5 mm | | | | | | | 1,5 | 1,5 | | | |
| | 2 mm | | 2 | 2 | 2 | 2 | 2 | | | 2 | | |
| | 3 mm | | | | 3 | 3 | 3 | 3 | 3 | | 3 | 3 |
| | 4 mm | | | | | 4 | 4 | | | 4 | | |
| | 4,5 mm | | | | | | | 4,5 | 4,5 | | | |
| | 5 mm | | | | | | 5 | | | | | |
| | 6 mm | | | | | | | 6 | 6 | 6 | 6 | 6 |
| | 7,5 mm | | | | | | | | 7,5 | | | |
| | 8 mm | | | | | | | | | 8 | | |
| | 9 mm | | | | | | | | | | 9 | 9 |
| | 10 mm | | | | | | | | | 10 | | |
| | 11,5 mm | | | | | | | | | | | 11,5 |
| | 12 mm | | | | | | | | | | 12 | |
| | 14,5 mm | | | | | | | | | | | 14,5 |
| | 15 mm | | | | | | | | | | 15 | |
| | 17,5 mm | | | | | | | | | | | 17,5 |
| 20,5 mm | | | | | | | | | | | 20,5 | |
| Mutterform | Zylindrisch | A | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Abgeflacht | A | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |

Bestellbeispiel **PWG 16** x **2** - **A 1**

Größe
 Spindelsteigung
 Mutterform